

Touch-Sensitive HD IP Conference Phone

Yealink CP925 is a touch-sensitive HD conference phone designed for small to medium conference room. CP925 adopts a business and introverted design that perfectly matches the calm style of the conference room, but also a acoustics fabric, which is impervious to any accidental liquid spills. Its fingerprint-proof LCD screen with a clear UI interaction page makes it easy for everyone to control the meeting. CP925 has 7 built-in microphones, providing you with a clear and natural conference call experience. In addition, you can connect CP925 to your mobile device (such as smartphone or PC) via Bluetooth to achieve a hybrid UC meeting.

As a valuable complement for your conference room, Yealink concentrates on users themselves, giving you an easy, clear, and engaging business conference experience.



4" Multi-Touch Screen



Yealink Pentagon Meeting Room



Hybrid UC Meeting



Pairing via Bluetooth



Key Features and Benefits

Modest Design, Easy-to-Use User Interface

Yealink CP925 is a hermit in the conference room. Its black acoustics fabric can realize crystal-clear audio and is resistant to water, oil, and stain. Its ultra-thin body, appropriate desktop fit, and ingenious hidden wiring slot, perfectly fit for the simple business style in the conference rooms. Additionally, its built-in Linux system and easy-to-use UI interface, allow users to launch a meeting with one button and increase user adoption.

HD Audio, Smooth Communication

CP925 adopts Y-shaped design and has 6 built-in microphones for sound pickup and 1 microphone for noise cancellation. Its 20-foot and 360° omni-direction sound pickup provide users with clear and natural voice conference experience.

Rich Features and High Expandability

CP925 supports 5-way conference call, enabling participants from different locations to communicate smoothly, reducing costs for your company. You can also connect CP925 to your mobile phone or PC through Bluetooth or to PSTN device CPN10 through USB-C to realize Hybrid UC meeting (including PSTN, SIP, mobile phone, and PC).

- 4-inch multi-touch screen with 480x800 resolution
- Optimal HD audio, full duplex technology
- Yealink Noise Proof Technology
- 20-foot (6-meter) and 360-degree voice pickup
- Built-in 6-microphone array for voice pickup
- Built-in 1-microphone array for noise cancellation
- Power over Ethernet
- 5-way conference call
- Hybrid UC meeting
- Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n)
- Built-in Bluetooth 4.2
- Local 3-way PSTN conference via Yealink CPN10

Audio Features

- Optimal HD audio
- Yealink Noise Proof Technology
- Smart Noise Filtering
- 20-foot (6-meter) microphone pickup range
- Apply to small to medium conference room
- Built-in 6-microphone array, 360-degree voice pickup
- Built-in 1-microphone array, decrease noise
- Loudspeaker
 - Frequency: 100-20,000 Hz
 - Volume: 94dB at 0.5-m peak volume
- 56mm diameter and 5w speaker
- Full-duplex speakerphone with AEC
- Echo cancellation tail length is up to 320ms
- Background noise suppression
- Codecs: G722, G722.1C, G726, G.729, G.729A, G723, iLBC, PCMU (G.711A), PCMA (G.711μ)
- DTMF: In-band, Out-of-band (RFC 2833) and SIP INFO
- VAD, CNG, PLC, AJB, AGC

Phone features

- 1 SIP account
- Call hold, mute, DND, call recording, hotline
- 5-way conference call
- Analog PSTN calls via CPN10
- Redial, call waiting, emergency call
- Call forward, call transfer, call return, dial plan
- Ring tone selection/import/delete
- Set date time manually or automatically
- Volume adjustment
- Pairing via Bluetooth
- Create meeting directly
- Join meeting seamlessly
- Active Speaker

Directory

- Local phonebook up to 1000 entries
- XML/LDAP remote phonebook
- Intelligent search method
- Phonebook search/import/export
- Call history: dialed/received/missed/forwarded
- Block list

IP-PBX features

- Busy Lamp Field (BLF)
- Multicast paging
- Intercom
- Anonymous call
- Anonymous call rejection
- Voice mail
- Distinctive ringtone
- Call pickup

Display

- 4" 480x800 capacitive touch screen
- Volume key
- Home button

Interface

- 1 x RJ45 10/100M Ethernet port
- Built-in Wi-Fi (2.4GHz/5GHz, 802.11a/b/g/n)
- Built-in Bluetooth 4.2
- Power over Ethernet (IEEE 802.3af), class 3
- 1 x USB 2.0 Type-C device port
- 1 x Security slot

Network and Security

- SIP v1 (RFC2543), v2 (RFC3261)
- SIP server redundancy supported
- IPv4/IPv6
- NAT traversal: STUN mode
- Proxy mode and peer-to-peer SIP link mode
- IP assignment: static/DHCP
- HTTP/HTTPS web server
- Time and date synchronization using SNTP
- UDP/TCP/DNS-SRV (RFC 3263)
- QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
- SRTP for voice encryption
- Transport Layer Security (TLS1.3)
- HTTPS certificate manager
- AES encryption for configuration file (AES256)
- Adb encryption authenticated
- Digest authentication using MD5/SHA1/SHA224/SHA256/SHA384/SHA512
- OpenVPN, L2TP VPN

- WPA2/WPA3
- Secure boot
- GARP (Generic Attribute Registration Protocol)

Management

- Configuration: browser/phone/auto-provision/Yealink Device Management Platform
- Auto provision via FTP/TFTP/HTTP/HTTPS for mass deploy
- Auto-provision with PnP
- Zero-sp-touch, TR-069
- Reset to factory, reboot
- Package tracing export, system log


Other physical features

- Color: Black
- External Yealink PoE adapter (optional)
- Power consumption (PSU): 3.5W-11W
- Power consumption (PoE): 4W-12W
- Dimension (W*D*H): 285mm*289.5mm*59.1mm
- Operating humidity: 10~90%
- Operating temperature: -10 to +45°C (+14 to 113°F)
- Storage temperature: -30 to +70°C (-22 to +158°F)


Package Features

- Package content:
 - Yealink CP925 IP conference phone
 - Ethernet Cable (7.5m CAT5E UTP cable)
 - M2x5 screw
 - Screwdriver
 - Yealink Power Adapter
 - Quick Start Guide
 - Yealink PoE Adapter YLPOE30 (Optional)
- Qty/CTN: 5 PCS
- N.W/CTN: 7.036 kg
- G.W/CTN: 8.106 kg
- Giftbox size: 355mm*349mm*108mm
- Carton Meas: 567mm*357mm*365mm


Compliance



Ⓐ AC Power Option



Ⓑ PoE (Power over Ethernet) Option



About Yealink

Yealink (Stock Code: 300628) is a global brand that specializes in video conferencing, voice communications and collaboration solutions with best-in-class quality, innovative technology and user-friendly experience. As one of the best providers in more than 140 countries and regions, Yealink ranks No.1 in the global market share of SIP phone shipments (Global IP Desktop Phone Growth Excellence Leadership Award Report, Frost & Sullivan, 2019).

Copyright

Copyright © 2021 YEALINK(XIAMEN) NETWORK TECHNOLOGY CO., LTD.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Yealink(Xiamen) Network Technology CO., LTD.

Technical Support

Visit Yealink WIKI (<http://support.yealink.com/>) for firmware downloads, product documents, FAQ, and more. For better service, we sincerely recommend you to use Yealink Ticketing system (<https://ticket.yealink.com>) to submit all your technical issues.



YEALINK(XIAMEN) NETWORK TECHNOLOGY CO.,LTD.
Web: www.yealink.com
Addr: No.1 Ling-Xia North Road, High Tech Park,
Huli District, Xiamen, Fujian, P.R.C
Copyright©2021 Yealink Inc. All rights reserved.